


SPRING ISOLATORS**SINGLE SPRING**M (25-550KG)

M	REF / ART.NR	DIMENSIONES / DIMENSIONS ABMESSUNGEN							COMPRESION / COMPRESSION DRUCKBELASTUNG		CONSTANTE / STIFFNESS RIGIDITE / STEIFIGKEIT		GRÁFICO DE SELECCIÓN
		ØA	B	C	D	E	F	G	M	CARGA / LOAD CHARGE / LAST	FLECHA / DEFLECTION FLECHE / FEDERWEG		
		mm.								kg.	mm.	kg./cm	
	M25	55	79						8	25	20±2,0	12,50	
	M50	55	79						8	50	20±2,0	25,00	
	M75	55	79						8	75	20±2,0	37,50	
	M100	55	79						8	100	20±2,0	50,00	
	M125	55	79						8	125	20±2,0	62,50	
	M150	73	116						12	150	30±3,0	50,00	
	M200	73	116						12	200	30±3,0	66,67	
	M250	73	116						12	250	30±3,0	83,33	
	M350	73	116						12	350	30±3,0	116,67	
	M450	73	116						12	450	30±3,0	150,00	
	M550	73	116						12	550	30±3,0	183,33	
	M25 B	55	81	90	55	70	10	10	8	25	20±2,0	12,50	
	M50 B	55	81	90	55	70	10	10	8	50	20±2,0	25,00	
	M75 B	55	81	90	55	70	10	10	8	75	20±2,0	37,50	
	M100 B	55	81	90	55	70	10	10	8	100	20±2,0	50,00	
	M125 B	55	81	90	55	70	10	10	8	125	20±2,0	62,50	
	M150 B	73	119	110	75	89	11	10	12	150	30±3,0	50,00	
	M200 B	73	119	110	75	89	11	10	12	200	30±3,0	66,67	
	M250 B	73	119	110	75	89	11	10	12	250	30±3,0	83,33	
	M350 B	73	119	110	75	89	11	10	12	350	30±3,0	116,67	
	M450 B	73	119	110	75	89	11	10	12	450	30±3,0	150,00	
	M550 B	73	119	110	75	89	11	10	12	550	30±3,0	183,33	
	M25 BB		83	90	55	70	10	10		25	20±2,0	12,50	
	M50 BB		83	90	55	70	10	10		50	20±2,0	25,00	
	M75 BB		83	90	55	70	10	10		75	20±2,0	37,50	
	M100 BB		83	90	55	70	10	10		100	20±2,0	50,00	
	M125 BB		83	90	55	70	10	10		125	20±2,0	62,50	
	M150 BB		120	110	75	89	11	10		150	30±3,0	50,00	
	M200 BB		120	110	75	89	11	10		200	30±3,0	66,67	
	M250 BB		120	110	75	89	11	10		250	30±3,0	83,33	
	M350 BB		120	110	75	89	11	10		350	30±3,0	116,67	
	M450 BB		120	110	75	89	11	10		450	30±3,0	150,00	
	M550 BB		120	110	75	89	11	10		550	30±3,0	183,33	

M



MB



MB8

